

View Online at <https://aerobasegroup.com/nsn/6625-01-458-5859>

**Circuit Current For Which Designed:**

Ac and dc

**Overall Depth:**

3.125 inches

**Overall Length:**

7.000 inches

**Overall Width:**

5.250 inches

**Scale Division Quantity:**

50 single indicator 2nd range

**Environmental Protection:**

Dust resistant and humidity resistant and vibration resistant

**Furnished Items And Quantity:**

Btry 2; color-coded test leads 2; screw-on clips 2; instruction manual 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Bench or hand held

**Sensitivity Rating:**

5.0 kilohm per volt and 20.0 kilohm per volt

**Dial Scale Marking Color:**

Green, light single indicator 1st range

**Accuracy In Percent:**

-3.0/+3.0 at full scale single indicator 9th range

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Red single indicator all ranges

**Power Source:**

External and internal

**Scale Graduation Type:**

Nonlinear single indicator 5th range

**Measurement Range:**

+0.0/+500.0 milliamperes, dc single indicator 7th range

**Scale Selection Method:**

Switch and terminal

**Features Provided:**

Electrical overload protection and internal battery accommodation and internal shunting and mirror scale and portable and rectifier circuit and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 banana jack and 2 banana plug

**Operating Voltage Rating In Volts:**

Between 1.5 dc and 9.0 dc

**Special Features:**

LACK-SO-VER-LOAD

**Special Markings:**

Black-sign, red + sign, below bottom scale

**Material:**

Plastic phenol-formaldehyde

**Style Designator:**

Portable

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0