

View Online at <https://aerobasegroup.com/nsn/6625-01-461-8299>

Current Type:

Ac and dc

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Frequency Range Rating:

+0.375/+173.500 megahertz

End Application:

Compatible with sonobuoy formats including an/ssq-36, an/ssq-41, an/ssq-47, an/ssq-48, an/ssq-50, an/ssq-53, an/ssq-57, an/ssq-62

Internal Battery Accommodation:

Included

Voltage Rating:

115.0 volts

Frequency Band Quantity:

31

Maximum Signal Output:

40 db below carrier-harmonically related; 60 db below carrier-nonharmonically related

Product Name:

Flightline acoustic test signal generator (atsg) sonobuoy simulator

Special Features:

99 channels; analog or fsk modulation; ten mile line-of-sight operating range; adjustable rf output level; front panel meters for rf and modulation level; built-in generation of difar, lofar, range, and b/t sonobuoy patterns; built-in fault isolation test; unit contains sg-1156/a aircraft signal generator

Functional Description:

Provides a signal source for flightline checkout and maintenance of airborne asw acoustic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-j