

View Online at <https://aerobasegroup.com/nsn/6625-01-462-6376>

Circuit Current For Which Designed:

Dc

Overall Depth:

1.500 inches

Overall Length:

8.000 inches

Overall Width:

3.500 inches

Furnished Items And Quantity:

Test leads 1; operating manual 1; 9v installed battery 1; holster 1; temperature adapter 1; type "k" temperature probe 1; rs-232 cable and software 1

Indicator Type:

Digital display

Installation Design:

Hand held

Display Type:

Liquid crystal

Display Digit Quantity:

4

Measurement Range:

+0.4/+1.0 volts, dc single indicator 3rd range

Accuracy Rating:

Porm 0.01 pct, porm 1.0 d all indicators all ranges

Display Color:

Red all indicators all ranges

Circuit Attachment Method And Quantity:

3 receptacle, coaxial

Operating Voltage Rating In Volts:

9.0 dc

Special Features:

10mhz frequency counter; true rms ac voltage and current readings; rs-232 interface and software for downloading measurements to a pc; decibel measurement; analog bargraph; 10 memory locations; time and stop watch mode with alarm; min. Max. Avg. And relative modes; capacitance and inductance measurement; temperature measurement in centigrade and fahrenheit; square wave output; continuity and diode test; warning buzzer and 20a fused socket; weights 1 pound

Relationship To Similar Equipment:

Similar to protec 505 however, protec 506 includes rs-232 interface

Style Designator:

Hand-held

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: