

View Online at <https://aerobasegroup.com/nsn/6625-01-464-1998>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

7.496 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.050 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.725 inches

**Overall Height:**

1.520 inches

**Overall Width:**

6.690 inches

**Mounting Hole Diameter:**

0.221 inches

**Environmental Protection:**

Cold resistant and drip proof and heat resistant and humidity resistant and shock resistant and vibration resistant

**Furnished Items And Quantity:**

Washer 6; nut 6

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

200.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

5.760 inches

**Meter Body Width Behind Mounting Flange:**

5.435 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Line at 0 and 100 pct points

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Meter Body Height Behind Mounting Flange:**

1.225 inches

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Plastic

**Style Designator:**

Rectangular flush mntg

**Supplementary Features:**

20 megohms insulation res

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0