NSN 6625-01-467-0363

Test Lead - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-467-0363

| Cross Sectional Shape: |
|--|
| Round |
| End Application: |
| Cass otps 1g |
| Termination Type: |
| Connector plug both ends single conductor |
| Leadlength: |
| 24.000 inches |
| Strand Quantity Per Conductor: |
| 65 single conductor or 40 single conductor |
| Conductor Form: |
| Stranded single conductor |
| Strand Awg Size Per Conductor: |
| 22 single conductor |
| Special Features: |
| Materials square socket; body, brass; springs, beryllium copper; insulation, heat shrinkable pvc; pin plug body, brass; handle, plastic; |
| lead wire is 22 awg 65 x 40 tinned copper with extra flexible thermoplastic insulation; finish, square socket springs gold plated; pin plug, |
| nickel plated; temperature range -55 degrees celsius to +85 degrees celsius |
| Material: |
| Copper core conductor all conductors and plastic core conductor all conductors |
| Precious Material And Location: |
| Square socket, springs gold |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A077a0 |
| |
| |
| |