

View Online at <https://aerobasegroup.com/nsn/6625-01-479-1643>

**Overall Length:**

19.000 inches

**Overall Height:**

3.500 inches

**Overall Width:**

13.000 inches

**Ac Voltage Rating:**

115.0 volts and 230.0 volts

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**End Application:**

This synthesized calibrato (346b add3) is part of the a/m99t-2, calibration trailer

**Internal Battery Accommodation:**

Not included

**Individual Channel Frequency:**

Between 0.1 kilohertz and 99.0 kilohertz

**Individual Channel Quantity:**

2

**Frequency Accuracy In Percent:**

+0.005/+0.010

**Internal Calibration Crystal:**

Included

**Phase:**

Single

**Special Features:**

Mfg name is synthesized calibrator. The pmel's using the 346b, (6625-01-424-2124) these calibrators are being upgraded. This upgrade adds a differential picocoulomb output to the calibrator, with this upgrade (add3) you can store 24 distinct setups each having 31 settings of frequency, amplitude and dwell time

**Functional Description:**

The a/m99t-2 calibration trailer is used to calibrate the vibration monitor/analyzers that are used in the a/m37t2 jet engine test stand

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T263-e