

View Online at <https://aerobasegroup.com/nsn/6625-01-493-2199>

Overall Length:

410.0 millimeters

Overall Height:

152.0 millimeters

Overall Width:

272.0 millimeters

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Voltage Rating:

Between 90.0 volts and 250.0 volts

Beam Quantity:

1

Screen Size:

6 inch rectangular

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+50.0/+200.0 megahertz

Single Trigger Sweep Duration:

10.0 nanoseconds

Trigger Sweep Voltage Amplitude Rating:

Between 2.0 millivolts and 5.0 millivolts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

1 nsec

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

5.0 millivolts peak to peak per centimeter

Horizontal Deflection Sensitivity Voltage Rating:

5.0 millivolts any acceptable megahertz

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

50.0 megahertz

Y-axis Frequency Response Rating:

50.0 megahertz

Amplifier Input Impedance Rating Provision:

Not provided

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-g