

View Online at <https://aerobasegroup.com/nsn/6625-01-502-4428>

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Voltage Rating:

Between 100.0 volts and 240.0 volts

Beam Quantity:

1

Screen Size:

8 by 10 centimeters

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+2.0/+10.0 megahertz

Single Trigger Sweep Duration:

5.0 nanoseconds

Trigger Sweep Voltage Amplitude Rating:

25.0 millivolts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

3.5 nsec

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

2.0 megahertz

Y-axis Frequency Response Rating:

2.0 megahertz

Amplifier Input Impedance Rating Provision:

Provided

Y-axis Input Impedance Rating:

50.0 ohms

Calibrated Screen Scale:

Included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Provided

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-g