

View Online at <https://aerobasegroup.com/nsn/6625-01-502-4428>

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Voltage Rating:**

Between 100.0 volts and 240.0 volts

**Beam Quantity:**

1

**Screen Size:**

8 by 10 centimeters

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Not included

**Sweep Circuit Type:**

Horizontal and vertical

**Sweep Frequency Range:**

+2.0/+10.0 megahertz

**Single Trigger Sweep Duration:**

5.0 nanoseconds

**Trigger Sweep Voltage Amplitude Rating:**

25.0 millivolts

**Trigger Sweep Polarity Switch:**

Included

**Trigger Sweep Marker Intervals:**

3.5 nsec

**Amplifier Deflection Sensitivity Provision:**

Not provided

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Not provided

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

2.0 megahertz

**Y-axis Frequency Response Rating:**

2.0 megahertz

**Amplifier Input Impedance Rating Provision:**

Provided

**Y-axis Input Impedance Rating:**

50.0 ohms

**Calibrated Screen Scale:**

Included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Provided

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T320-g