

View Online at <https://aerobasegroup.com/nsn/6625-01-516-8477>

Unit Type:

Standard

Special Features:

Speed sweep time less than 3 ghz 1 ms to 4000 s; zero span sweep time 50 ns to 4000 s; local measurement rate 50 sec; remote measurement and transfer rate 45 sec; rf center frequency tuning time 75 ms; warm-up time for full accuracy 5 min; resolution resolution bandwidth range 1 hz to 5 mhz; residual fm 2 hz p-p in 20 ms; phase noise, 10 khz/1 mhz offsets, minus 93 dbc/hz; variable sweep, trace, point range 101 to 8192; dynamic range amplitude measurement range minus 165 dbm to plus 30 dbm; calibrated display range 85 to 120 db; maximum 2nd order dynamic range 92 db, plus 35 dbm shi; maximum 3rd order dynamic range 109 db, plus 13.5 dbm toi; 1-db gain compression 0 dbm; accuracy frequency accuracy, stable temp, porm 101 hz; span accuracy, 8192 sweep points; absolute amplitude accuracy porm 1.0 db; 9 khz to 1.5 ghz

Functional Description:

Uses the latest digital rf and microwave designs; portable; one-millisecond rf sweep time and virtual real time measurement updates to the display or through gpib, along with narrow digital resolution bandwidth filters, 1 hz to 300 hz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A532p0