

View Online at <https://aerobasegroup.com/nsn/6625-01-521-3682>

**Overall Depth:**

16.750 inches

**Overall Height:**

5.250 inches

**Overall Width:**

8.500 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Voltage Rating:**

Between 100.0 volts and 240.0 volts

**Screen Size:**

8 by 10 centimeters

**X-axis Input Impedance Rating:**

1.0 megohms

**Y-axis Input Impedance Rating:**

1.0 megohms

**Z-axis Input Impedance Rating:**

1.0 megohms

**Phase:**

Single

**Special Features:**

8crt display spot size 0.26 mm at 0.5, ua beam current 25 foot lamberts at 200 line raster and 60hz refresh rate: z-axis bandwidth dc to 4mhz, maximum input voltage 100 volts (dc plus ac peak), rise time less than 90ns: x-y deflection bandwidth dc to 3 mhz, dc coupling required, phase shift less than 3 degrees at 1mhz sensitivity: 100mv/div, adjustable plus or minus 50 percent, linearity within 5 percent, maximum input voltage 100 volts (dc plus ac peak), rise time less than 120ns; mfg name x-y display monitor

**Reference Data And Literature:**

33d7-50-2648-2

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T320-g