

View Online at <https://aerobasegroup.com/nsn/6625-01-524-7163>

Width:

11.000 inches

Ac Voltage Rating:

110.0 volts

Frequency Rating:

Between 20.0 hertz and 120.0 kilohertz

Depth:

9.000 inches

Internal Battery Accommodation:

Included

Product Name:

Transmission test set 806d

Special Features:

Front panel controls come w/ bright led displays and indicators; include software that runs under dos or a dos window under windows operating systems; pc communicates w/ test set through a rs-232 port; level is measured in dbm w/ power relative to 1 milliwatt; noise measured in dbrn w/ power relative to 1 pcw, or dbm; filters w/applications include, c msg-pots voice traffic, 3khz-pots power line/ringing interference, 15khz-modem traffic/program noise, 1010 notch-pots s/n ratio / noise or s/n on pcm, program-broadcast quality audio facilities and 50k-bit; t.O. 33a1-13-129-1

Functional Description:

Used to measure level, p/ar, noise, noise w/ tone, signal/ noise ratio, noise to ground, impulse noise and frequency iaw ieee standard 743-1984

Height:

3.500 inches

Relationship To Similar Equipment:

Similar to hp4934a transmission impairment measuring set and hp4935a transmission test set

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T228-a