

View Online at <https://aerobasegroup.com/nsn/6625-01-527-5543>

**Circuit Current For Which Designed:**

Ac or dc

**Overall Depth:**

7.100 inches

**Overall Length:**

17.500 inches

**Overall Width:**

11.500 inches

**Environmental Protection:**

Dust resistant and waterproof

**Furnished Items And Quantity:**

One pair test probes: heavy duty pistol grip probes, each with two durable hardened tips which rotate when pressed against the surface to be tested. Each probe comes with right feet of number 12 awg two-wire cable with color coded spade lugs. Three atex approved alkaline "d" cells, operations and maintenance manual.

**Indicator Type:**

Digital display

**Installation Design:**

Bench

**Power Source:**

Internal

**Display Type:**

Liquid crystal

**Display Digit Quantity:**

3-1/2

**Measurement Range:**

+0.0/+199.9 ohms single indicator all ranges

**Scale Selection Method:**

Switch

**Accuracy Rating:**

0.1% of reading +/- two counts on all ranges single indicator all ranges

**Display Color:**

Gray single indicator all ranges

**Circuit Attachment Method And Quantity:**

2 wire lead

**Special Features:**

The ppm model r11-e2 is a portable ohmmeter designed to measure low values of resistance, from 1 micro ohm to 20 ohms, in explosive atmospheres. Applications include aircraft fuel tank, fuel storage and transportation line bond testing

**Special Test Features:**

Certifications include; u1913; csa e79-0; csa e79-11; ce certified; atex directive (94/9/eec); en 50014, 1997 edition, including amendment 2; en 50020, 2002 edition; en 50284, 1999 edition; en61326, 1997 edition including amendment 1; 1998 and amendment 2: 2001; explosive atmosphere per mil-pre-28800f

**Style Designator:**

Portable

**Shelf Life:**

N/a

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0