

View Online at <https://aerobasegroup.com/nsn/6625-01-547-2058>

**Circuit Current For Which Designed:**

Dc

**Overall Depth:**

60.0 millimeters

**Overall Length:**

195.0 millimeters

**Overall Width:**

92.0 millimeters

**Frequency Rating:**

Between 40.0 hertz and 20000.0 hertz

**Indicator Type:**

Digital display and bargraph

**Installation Design:**

Hand held

**Background Color:**

Blue single indicator all ranges

**Power Source:**

External

**Display Type:**

Liquid crystal

**Display Digit Quantity:**

4-3/4

**Measurement Range:**

+1000.0/+1000000.0 ohms single indicator 7th range

**Scale Selection Method:**

Switch

**Features Provided:**

Autorange and electrical overload protection and internal battery accommodation

**Accuracy Rating:**

Porm 5.0 pct of reading plus 30 digits single indicator 3rd range

**Operating Voltage Rating In Volts:**

5.0 dc

**Special Features:**

Additional electrical characteristics - ac current 0.4 amps at plus or minu (porm) 2.0 pct. Of reading plus 10 digits, 10.0 amps at porm 2.5 pct. Of reading plus 10 digits; dc current: 10.0 amps at porm 1.5 pct. Of reading plus 10 digits; resistance: 10.0 megaohms porm 1.0 pct. Of reading plus 10 digits, 40.0 megaohms porm 2.0 pct. Of reading plus 10 digits; dc current: 100.0 microamps porm 0.5 pct. Of reading plus 10 digits; volts ac: 750.0 volts porm 2.0 pct. Of reading plus 10 digits; specifications at plus 23.0 degrees c. Porm 5.0 degrees with less than 75.0 pct. Relative humidity non-condensing; operating temperature 0.0 to 45.0 degrees c. At less than 70.0 pct. Relative humidity; storage temperature minus 20.0 to 60.0 degrees c. At 80.0 percent relative humidity with battery removed from meter; altitude 2000.0 meters; weight 450.0 grams

**Style Designator:**

Hand-held

**Shelf Life:**

N/a

**Unit Of Measure:**

**Fig:**

A310a0