

View Online at <https://aerobasegroup.com/nsn/6625-01-550-2457>

Overall Depth:

460.0 millimeters

Overall Height:

192.0 millimeters

Overall Width:

435.0 millimeters

Ac Voltage Rating:

100.0 volts or 240.0 volts

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Frequency Range Rating:

+0.000/+26.500 gigahertz

End Application:

Vdats

Input Impedance Rating:

50.0 ohms

Unit Type:

Standard

Mounting Method:

Rack

Extra Long Reference Number:

Fsu26 opt-b23-b25-k7-k30-k40-zza411

Functional Classification:

Aa-3.3

Special Features:

Actual frequency range is 20hz to26.5 ghz dc coupled, 10mhz to 26.5ghz ac coupled, has 8.4 inch liquid crystal tft color display with svga resolution, stores more than 500 instrument settings and traces, options included with this item are: (optb23 requiring opt b25) 0 to 30db electronic attenuator, and 20db preamp 3.6hz to 26.5ghz, (optk7) fm measurement de-modulator, (optk30) noise figure and gain measurement firmware, (optk40) phase noise measurement firmware, (optzza411) 19 inch rack adapter, also has probe power supply connection, antenna power supply connection, supply voltages are 15vdc, -12.6vdc, +/- 10vdc, and ground, ps/2 female connection for mf-2 keyboard

Reference Number Differentiating Characteristics:

Differentiated by options

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A532p0