

View Online at <https://aerobasegroup.com/nsn/6625-01-556-6946>

Mounting Type:

Rack

Overall Length:

450.0 millimeters

Overall Height:

133.0 millimeters

Overall Width:

429.0 millimeters

Current Type:

Ac

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Frequency Range Rating:

+2.000/+20.000 gigahertz

End Application:

Radt (radar avionics depot test station)

Output Impedance Rating:

50.0 ohms

Voltage Rating:

Between 85.0 volts and 264.0 volts

Modulation Type:

Am and fm and pulse

Fixed Frequency Rating:

10.000 megahertz

Fixed Frequency Quantity:

1

Maximum Signal Output:

+19.0dbm from 10mhz to 20ghz

Modulator Location:

External

Extra Long Reference Number:

Mg3692b-1b-2a-3-5-6-12-13a-14-sm5815

Phase:

Single

Functional Classification:

Bb-1.1

Special Features:

Includes the following options: (1b)rackmount without slides; includes mounting ears and handles, (2a)mechanical step attenuator, (3)ultra low phase noise, (5)extends freq range down to 10mhz, (6)analog sweep, (12)external frequency and phase modulation, (13a)external pulse modulation, (14)external amplitude modulation, (sm5815) external 100mhz reference

Specification Data:

81349-mil-prf-2880 government specification

Reference Number Differentiating Characteristics:

As differentiated by part number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-j

Mil-std (military Standard):

Mil-prf-2880 spec.