NSN 6625-01-560-5674 Cable Shield Resistance Test Set - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-560-5674  Width: 3.940 inches  Length: 8.000 inches  Ac Voltage Rating: Between 0.1 volts and 600.0 volts  Dc Voltage Rating:
3.940 inches  Length: 8.000 inches  Ac Voltage Rating: Between 0.1 volts and 600.0 volts
Length: 8.000 inches Ac Voltage Rating: Between 0.1 volts and 600.0 volts
8.000 inches  Ac Voltage Rating:  Between 0.1 volts and 600.0 volts
Ac Voltage Rating: Between 0.1 volts and 600.0 volts
Between 0.1 volts and 600.0 volts
Dc Voltage Rating:
Between 0.1 volts and 600.0 volts
Frequency Rating:
Between 50.0 hertz and 400.0 hertz
Accessory Component Quantity:
6
End Application:
Water purification unit
Electrical Power Source Relationship:
Operating
Test Type For Which Designed:
Insulation resistance
Product Name:
Fluke 1503 insulation resistance tester
Special Features:
Measurement range: 0.01 to 2000 mega ohm; test voltage: 500v, 1000v; storage temperature: negative 40 to 60 degree celsius; oper
temperature: negative 20 to 55 degree celsius; requires 4 aa batteries; weight: 1.2 lb; ip rating: ip40; included accessories: tl224 test
leads, tp74 test probes, clips p/n 195865 (red) and p/n 1958646(black), holster and remote probe
Height:
1.970 inches
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No No
Fiig:
T228-a