

View Online at <https://aerobasegroup.com/nsn/6625-01-566-5214>

Current Type:

Ac

Frequency Rating:

Between 47.0 hertz and 470.0 hertz

End Application:

Spacelift range systems (slrs)

Electrical Connection Type:

Bnc and connector receptacle

Voltage Rating:

Between 90.0 volts and 265.0 volts

Electrical Connection Quantity:

5

Mounting Method:

Rack

Measurement Type:

Time

Display Type:

Light emitting diode

Display Digit Quantity:

28

Display Units Indicator:

Included

Display Positioned Decimal Point:

Provided

Remote Control Provisions:

Included

Product Name:

Central command system countdown display

Special Features:

Inputs: irig-b modulated code 10mv pkpk at 10kohm; cs-524x or cs5x4 at 4.8/9.6/19.2 kbaud (auto detect baud rate), outputs: cs-5xxx buffered out; cs-524x (2ea) rs-422 on twinax connectors (left and right side display), unit has two independant 14 character displays (1 left / 1 right); displays either event count or launch time; unit has dual power supplies

Relationship To Similar Equipment:

Similar to 6625-01-554-2576 except this unit has dual power supplies

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T297-a