

View Online at <https://aerobasegroup.com/nsn/6625-01-567-5672>

Circuit Current For Which Designed:

Ac

Overall Length:

155.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.284 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches

Overall Height:

105.0 millimeters

Overall Width:

65.0 millimeters

Mounting Hole Diameter:

6.0 millimeters

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

End Application:

Used on spearfish torpedo rate system

Indicator Type:

Digital display

Installation Design:

Cabinet

Mounting Arrangement Style:

Four hole/stud rectangular/square

Background Color:

Blue single indicator single range

Scale Marking:

30/80 bar range selector

Mounting Facility Type And Quantity:

8 threaded hole

Display Type:

Liquid crystal

Display Digit Quantity:

8

Accuracy Rating:

Porm 0.010 pct fs accuracy single indicator single range

Display Color:

Blue single indicator single range

Circuit Attachment Method And Quantity:

1 connector, plug

Operating Voltage Rating In Volts:

Between 100.0 ac and 240.0 ac

Special Features:

Used for controlled pressure measurement tests on spearfish torpedo; consists of model 6100 digital pressure transducer; remote pressure lcd display unit model 9420; desktop single board computer; external power supply

Style Designator:

Rectangular or square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0