

View Online at <https://aerobasegroup.com/nsn/6625-01-585-4363>

Circuit Current For Which Designed:

Ac and dc

Overall Depth:

4.000 inches

Overall Height:

8.500 inches

Overall Width:

14.000 inches

Frequency Rating:

60.0 hertz

Indicator Type:

Digital display

Installation Design:

Bench

Display Type:

Liquid crystal

Display Digit Quantity:

6-1/2

Measurement Range:

+0.0/+1000.0 volts single indicator all ranges

Criticality Code Justification:

Supp

Circuit Attachment Method And Quantity:

5 jack tip

Operating Voltage Rating In Volts:

115.0 ac

Interface Compatibility:

Rs-232-c

Phase:

Single

Functional Classification:

Aa-1.4

Special Features:

11 measurement functions; 1000v ac/dc input; 15ppm accuracy; 1000 readings per second; hp-1b and rs-232 interface; spci command standard; input voltage 100/120/220/240; line frequency 48 to 66 and 360 to 440; accessories include test kit leads, operators manual, service manual, power cord

Entry Date:

10-05-26

Style Designator:

Portable w/tilt view handle

Supplementary Features:

Characteristics such as form, fit, function and application are critical to the nha applications an/alm-233 and an/alm-256. This p/n is required to be compatible with cpin 85b-alm233/184-u001-00a and 85b-alm256v-t001-00a

Reference Number Differentiating Characteristics:

Procurement control drawing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0