

View Online at <https://aerobasegroup.com/nsn/6625-01-585-9036>

**Mounting Type:**

Rack

**Overall Length:**

450.0 millimeters

**Overall Height:**

133.0 millimeters

**Overall Width:**

429.0 millimeters

**Current Type:**

Ac

**Frequency Rating:**

Between 48.0 hertz and 440.0 hertz

**Frequency Range Rating:**

+2.000/+20.000 gigahertz

**End Application:**

An/alm-233 and an/alm-256

**Output Impedance Rating:**

50.0 ohms

**Voltage Rating:**

Between 85.0 volts and 264.0 volts

**Maximum Signal Output:**

+19.0dbm from 10mhz to 20ghz

**Criticality Code Justification:**

Supp

**Phase:**

Single

**Functional Classification:**

Bb-1.1

**Special Features:**

Options -1a rackmount kit with slides; -2a mechanical step attenuator; -5 10mhz to 2ghz rf coverage, analog down converter; -6 analog sweep capability; -14 external amplitude modulation; -26a external pulse modulation; -sm622 special firmware, 6700 compatibility

**Supplementary Features:**

Characteristics such as form, fit, function and application are critical to the nha applications an/alm-233 and an/alm-256. This p/n is required to be compatible with cpin 85b-alm233/184-u001-00a and 85b-alm256v-t001-00a

**Reference Number Differentiating Characteristics:**

Procurement control drawing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T320-j