

View Online at <https://aerobasegroup.com/nsn/6625-01-614-0547>

End Application:

Pete

Furnished Items And Quantity:

1 each unless noted: soft carrying bag; rechargeable nimh batteries; power adapter 110v/240v with power cord 115v us; user manual; dataview software cd; hard carrying case; two 300 ft color-coded leads on spools (red and blue); five termination spade lugs; two 100 ft color-coded leads (green and black); four t-shaped stainless steel auxilliary ground rods; dc power supply, 24 vdc; two 5 ft color coded leads (red and blue); pair of lineman's electrical insulated gloves (ansi/astm class 00)

Indicator Type:

Digital display

Installation Design:

Hand held

Dial Scale Marking Color:

Black single indicator all ranges

Background Color:

Blue single indicator all ranges

Power Source:

Internal

Display Type:

Liquid crystal

Display Digit Quantity:

4

Measurement Range:

+0.1 to 6.5 volts, ac single indicator 3rd range

Scale Selection Method:

Terminal

Features Provided:

Internal battery accommodation and portable

Circuit Attachment Method And Quantity:

5 banana jack and 5 crimp lug

Product Name:

Ground resistance tester model 6470-b - 150 ft

Special Features:

Meter contained in hard case (suitcase style) has lcd screen, receptacles for terminals and control buttons in bottom half; upper half has screen where reports are shown; kit includes items in akyn statement plus meter; all fit in duffle style carrying bag (included)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0