

View Online at <https://aerobasegroup.com/nsn/6625-01-616-6188>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Reliability Indicator:

Established

Overall Length:

2.000 inches

Mounting Hole Diameter:

0.125 inches

Overall Diameter:

2.675 inches

Mounting Bolt Circle Diameter:

2.440 inches

End Application:

7010-01-600-6765

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

+0.0 to 50.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 50.0 volts single indicator single range

Accuracy Rating:

2 single indicator single range

Circuit Attachment Method And Quantity:

3 threaded stud

Operating Voltage Rating In Volts:

50.0 dc

Product Name:

Voltmeter

Material:

Plastic

Material Specification:

Mil-prf-10304f military specification single material response and mil-prf-10304/4 military specification single material response

Style Designator:

C1 round flush mtg

Specification Data:

81349-mil-prf-10304f government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0

Mil-std (military Standard):

Mil-prf-10304f spec.