

View Online at <https://aerobasegroup.com/nsn/6625-01-624-7736>

Circuit Current For Which Designed:

Ac

Overall Depth:

25.0 millimeters

Overall Length:

12.5 millimeters

Overall Width:

10.0 millimeters

Indicator Type:

Digital display

Installation Design:

Hand held

Display Type:

Light emitting diode (I.E.D.).

Display Digit Quantity:

4

Measurement Range:

+100.0 to 500.0 volts all indicators all ranges

Accuracy Rating:

I6 all indicators all ranges

Display Color:

Black all indicators all ranges

Circuit Attachment Method And Quantity:

1 probe

Product Name:

Multifunctional instalation tester

Special Features:

Weight: 1.5kg, battery size, quantity: type aa-6ea, fuse: t3.15a, 500v, 1.5ka 6.3x32mm, operating temp: -10 degree c to 40 degree c, storage temp: -10 degree c to 60 degree c indefinitely (to-40 degree c for 100 hrs), operating altitude: 0 - 2000 meters, shock, vibration: vibration to class 3 per mil-prf-28800f 1 meter drop test, six sides, oak floor, sealing: ip 40, surge protection: 6 kv peak per en 61010-1 ed. 2.0.

Style Designator:

Portable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0

Mil-std (military Standard):

Mil-prf-28800f spec.