

View Online at <https://aerobasegroup.com/nsn/6625-01-645-9571>

Circuit Current For Which Designed:

Ac

Overall Length:

11.0 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.376 inches

Overall Height:

Between 4.250 inches and 4.750 inches

Overall Width:

Between 4.250 inches and 4.750 inches

Scale Division Quantity:

30 single indicator single range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5 to 1.5 at full scale single indicator single range

Panel For Which Designed:

Magnetic

Meter Depth Behind Mounting Flange:

10.0 inches

Meter Body Diameter Behind Mounting Flange:

3.980 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.250 inches

Scale Selection Method:

Switch

Features Provided:

Magnetic shield and zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Product Name:

A.C. Ammeter

Style Designator:

Rectangular flush mtg

Test Data Document:

81349-mil-m-16034 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0