

View Online at <https://aerobasegroup.com/nsn/6625-01-647-4855>

Circuit Current For Which Designed:

Ac and dc

Overall Depth:

10.7 inches

Overall Height:

2.3 inches

Overall Width:

5.0 inches

Frequency Rating:

Between 40.0 hertz and 1000.0 hertz

Indicator Type:

Digital display

Installation Design:

Hand held

Power Source:

Internal

Mounting Facility Type And Quantity:

1 clamp

Display Type:

Light emitting diode (I.E.D.).

Display Digit Quantity:

8

Features Provided:

Internal battery accommodation

Display Color:

Gray, light 1st indicator 1st range

Circuit Attachment Method And Quantity:

1 probe

Operating Voltage Rating In Volts:

600.0 ac

Product Name:

Power clamp meter

Phase:

Three

Special Features:

9999 count lcd; ac+dc ?A current with 10na resolution for flame rod test; max/min recording with elapsed time indication; auto detect ac/dc voltage measurements with simultaneous frequency display; capacitance to 7000?F with 0.001 ?F resolution; high resistance tests to 100mohm; type k, ?C/?F switchable, temperature to 1000?F; diode and continuity tests; 1.6" (40mm) clamp jaw opening complete with test leads type k probe (-58 to 482?F/ -50 to 250?C), carrying case and 9v battery; phase angle with lead/lag indicator

Material:

Plastic

Style Designator:

Clamp-on

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0