

View Online at <https://aerobasegroup.com/nsn/6625-01-647-4855>

**Circuit Current For Which Designed:**

Ac and dc

**Overall Depth:**

10.7 inches

**Overall Height:**

2.3 inches

**Overall Width:**

5.0 inches

**Frequency Rating:**

Between 40.0 hertz and 1000.0 hertz

**Indicator Type:**

Digital display

**Installation Design:**

Hand held

**Power Source:**

Internal

**Mounting Facility Type And Quantity:**

1 clamp

**Display Type:**

Light emitting diode (I.E.D.).

**Display Digit Quantity:**

8

**Features Provided:**

Internal battery accommodation

**Display Color:**

Gray, light 1st indicator 1st range

**Circuit Attachment Method And Quantity:**

1 probe

**Operating Voltage Rating In Volts:**

600.0 ac

**Product Name:**

Power clamp meter

**Phase:**

Three

**Special Features:**

9999 count lcd; ac+dc ?A current with 10na resolution for flame rod test; max/min recording with elapsed time indication; auto detect ac/dc voltage measurements with simultaneous frequency display; capacitance to 7000?F with 0.001 ?F resolution; high resistance tests to 100mohm; type k, ?C/?F switchable, temperature to 1000?F; diode and continuity tests; 1.6" (40mm) clamp jaw opening complete with test leads type k probe (-58 to 482?F/ -50 to 250?C), carrying case and 9v battery; phase angle with lead/lag indicator

**Material:**

Plastic

**Style Designator:**

Clamp-on

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0