

View Online at <https://aerobasegroup.com/nsn/6630-01-300-8711>

**Height:**

360.0 millimeters

**Current Type:**

Ac

**Frequency Rating:**

50.0 hertz or 60.0 hertz

**Accessory Components And Quantity:**

Potassium electrodes, 1; sodium electrode, 1; reference electrode, 1; bottle of standard a, 2; bottle of standard b, 1; waste bottle, 1; bottle of reference filling solution, 1; bottle of test dye solution, 1; reference membrane assembly, 2; fluid path module, 1; bottle electrode rinse solution, 1; slide valve, 1; sample probe assembly, 1; reusable storage container, 1

**Features Provided:**

Digital display screen and integral printer and self-calibration

**Product Name:**

Analyzer potassium and sodium ion selective:

**Method Of Analysis:**

Potentiometric/ion selective electrode

**Electrode Type:**

Potassium/k+ and reference and sodium/na+

**Analysis Test/measurement Range:**

Sodium 100-170 mmol/l in blood and 14-1400 mmol/l in undiluted urine; potassium 2-7 mmol/l in blood and 0.4-400 mmol/l in undiluted urine

**Test Sample/specimen Size:**

100 microliters of blood or 400 microliters of prediluted urine

**Err Default:**

Err default

**Test Sample/specimen Type:**

Whole blood, serum, plasma, and urine

**Depth:**

230.0 millimeters

**Voltage In Volts:**

120.0 or 230.0

**Special Features:**

If the analyzer does not contain an integral printer, it shall be capable of interfacing w/a commercially available external printer

**Unit Of Issue Cube:**

2.820 cubic feet

**Unit Of Issue Weight:**

29.00 pounds

**Width:**

260.0 millimeters

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A503u0