NSN 6630-01-603-2778

Photoelectric Colorimeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6630-01-603-2778

Voltage	In	Volte	Δnd	Current	Tyne:
v Oitage		VOILS	Allu	Current	ıype.

3.7 dc

Product Name:

Smart3 colorimeter

Special Features:

For water analysis in the field or in the lab; test factors can be arranged in any of three sequences that can be modified at any time to meet changing testing needs; data logger holds up to 500 time and date stamped data points usb connection allows an interface of the colorimeter with a computer for real-time data acquisition and data transfer; 160 x 100 backlit liquid crystal 20 x 6 line graphical display; detectors; 4 silicon photodiodes w/ integrated interference filters; sample chamber: 25 mm diameter flat bottom test tubes, 10 mm square cuvettes, 16 mm cod tubes; usb port: mini b; power: lithium ion rechargeable battery, 3.7 v, 2.5 x 0.75 in or usb computer cable or wall adapter; dimensions: 3.5 x 7.5 x 2.5 in; includes: colorimeter, 6 sample tubes, cod/udv adapter, usb wall/computer adapter, usb cable, quick start guide, and manual

_					
•	he	·I+		18	ο.
J	ııc	;	_		┖.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900