

View Online at <https://aerobasegroup.com/nsn/6635-00-530-0009>

**Mounting Type:**

Floor

**Current Type:**

Ac

**Prime Mover Horsepower Rating:**

1.0

**Drive Type:**

Belt

**Angular Unbalance Location Method:**

Graduated dial

**Maximum Working Weight Capacity:**

300.0 pounds

**Minimum Working Weight Capacity:**

15.0 pounds

**Swing Maximum Diameter:**

24.000 inches

**Maximum Distance Between Bearing Shoulders:**

24.000 inches

**Shaft Maximum Diameter At Bearing:**

5.000 inches

**Work Support Type:**

Half bearing

**Vibration Sensitivity Rating:**

0.000025 inches

**Integral Correction Drilling Attachment:**

Not included

**Unpackaged Unit Weight:**

1800.000 pounds

**Voltage In Volts:**

220.0

**Functional Classification:**

Aa-8.9

**Frequency In Hertz:**

60.0

**Functional Description:**

Elect device used to locate & meas unbalance in rotating parts or assemblies which weigh btwn 15 & 300 lb

**Entry Date:**

70-04-01

**Reference Data And Literature:**

Gisholt catalog

**Relationship To Similar Equipment:**

INTE-RC-HAN-GEAB

**Type/model Designation:**

3s

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T137-e