Horizontal Dynamic-static Balancing Machine - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6635-00-530-0009

| Mounting Type: |
|---|
| Floor |
| Current Type: |
| Ac |
| Prime Mover Horsepower Rating: |
| 1.0 |
| Drive Type: |
| Belt |
| Angular Unbalance Location Method: |
| Graduated dial |
| Maximum Working Weight Capacity: |
| 300.0 pounds |
| Minimum Working Weight Capacity: |
| 15.0 pounds |
| Swing Maximum Diameter: |
| 24.000 inches |
| Maximum Distance Between Bearing Shoulders: |
| 24.000 inches |
| Shaft Maximum Diameter At Bearing: |
| 5.000 inches |
| Work Support Type: |
| Half bearing |
| Vibration Sensitivity Rating: |
| 0.000025 inches |
| Integral Correction Drilling Attachment: |
| Not included |
| Unpackaged Unit Weight: |
| 1800.000 pounds |
| Voltage In Volts: |
| 220.0 |
| Functional Classification: |
| Aa-8.9 |
| Frequency In Hertz: |
| 60.0 |
| Functional Description: |
| Elect device used to locate & meas unbalance in rotating parts or assemblies which weigh btwn 15 & 300 lb |
| Entry Date: |
| 70-04-01 |
| Reference Data And Literature: |
| Gisholt catalog |
| Relationship To Similar Equipment: |
| INTE-RC-HAN-GEAB |



Horizontal Dynamic-static Balancing Machine - Page 2 of 2



Type/model Designation:

3s

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

Т137-е