## NSN 6635-00-634-9270

Horizontal Dynamic-static Balancing Machine - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/6635-00-634-9270



| Mounting Type:                              |
|---|
| Floor                                       |
| Current Type:                               |
| Ac  |
| Prime Mover Horsepower Rating:              |
| 2.0   |
| Drive Type:                                 |
| Universal coupling                          |
| Angular Unbalance Location Method:          |
| Graduated dial                              |
| Maximum Working Weight Capacity:            |
| 100.0 pounds                                |
| Minimum Working Weight Capacity:            |
| 100.0 pounds                                |
| Swing Maximum Diameter:                     |
| 66.000 inches                               |
| Maximum Distance Between Bearing Shoulders: |
| 66.000 inches                               |
| Work Support Type:                          |
| Half bearing                                |
| Vibration Sensitivity Rating:               |
| 0.000025 inches                             |
| Integral Correction Drilling Attachment:    |
| Not included                                |
| Voltage In Volts:                           |
| 220.0                                       |
| Phase:                                      |
| Three                                       |
| Frequency In Hertz:                         |
| 60.0  |
| Shelf Life:                                 |
| N/a   |
| Unit Of Measure:                            |
|   |
| Demilitarization:                           |
| No  |
| Fiig:                                       |
| T137-e                                      |