NSN 6635-00-735-2622

Torque Wrench Tester - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6635-00-735-2622

| Torque Indicating Mechanism: |
|--|
| Dial |
| Torque Capacity: |
| Between 0.0 inch-ounces and 800.0 inch-ounces |
| Torque Scale Graduation: |
| 0.10 inch-ounces |
| Torque Signal Method: |
| Dial indicator |
| Drive Surface Size: |
| 0.250 inches single end |
| Drive End Shape: |
| Hexagon single end external |
| Special Features: |
| Dual range 0-50 in-lb & 0-800 in-oz in increments of 0.05 in-lb to 1.0 oz; 14 lbs; 2 standard adapters of 0.25 in & 0.375 in; single station |
| type 1a; accuracy porm 1 pct; op temp 32-25deg f measures static torque; verifiesaccuracy of dial, free wheeling, click type & light &/or |
| sound indicating torque wrenches/screwdrivers; adjusts torque; calibrates; verifies setting overload of pressure, force or voltage on |
| clutches/brakes; measures frictions torque in bearings/gear trains; measures sstalling torque on electric, air, hydraulic motors |
| Material: |
| Aluminum |
| Specification Data: |
| 81349-mil-t-26639 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A102a0 |
| |
| |
| |
| |