

View Online at <https://aerobasegroup.com/nsn/6635-00-994-2157>

**Current Type:**

Ac

**Accessory Components And Quantity:**

Operation and maintenance manual 1; tube head ruggedized transit case 1; controller ruggedized transit case 1; cooler ruggedized transit case 1; cabling and hose ruggedized transit case 1; 2 extra keys for control unit safety lock 1; power cable assembly 100 ft with strain relief 1; control cable assembly 100 ft with strain relief 1; cooler power cable 50 ft with strain relief 1; coolant hose-twin, 50 ft, self-sealing g connector 1; lightweight laser pointer, removable, to provide precise targeting of x-ray beam up to 50ft

**Current Rating In Amps:**

10.0

**Design Type:**

Portable

**Operation Method:**

Manual

**Control Type:**

Mobile

**Tube Quantity:**

1

**Tube Type:**

Single focus

**Tube Cooling Method:**

Water

**Tube Mounting Type:**

Tube stand

**Tube Stand Mounting Type:**

Base

**Radiographic Timer Type:**

Exposure

**Err Default:**

Err default

**Voltage In Volts:**

100.0 and 250.0

**Phase:**

Single

**Special Features:**

160kvcp; x-ray tube head-directional, constant potential, end-grounded, gas insulated; control unit-digital microcomputer based; tube window 0.093 in. Thick; beamangle from side w/approx 40 degrees cone of radiation

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**