NSN 6635-01-103-3380

Fluorescent Penetrant Inspection Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6635-01-103-3380

Special Features:

Shelf Life:

C/o penetrant, penetrant drain, emulsification, emulsification drain, rinse, developer, developer drain, hot air recirculating dryer, cooler, and inspection stations; station size 43 in. Lg, 29 in. W, 26 in. H; structural steel frame angles, 16 gage carbon stl tanks; 50-500 degrees f thermostat control; 220 or 440v; built-in transformer 110 or 120v 1 phase, 60 hz; rinse station c/o frame, tank, cover, junction box, black light, hand hose w/nozzle; frame: 34 in. W, 48 in. Lg, 36 in. H; dryer station c/o frame (34 in w, 48 in. Lg, 36 in. H), hot air elec dryer cabinet w/full roller grill, 8000 w heater, 2 fans; inspection station c/o frame, full roller grille, table top, dust pan, exhaust fan, 2 black lights, junction box, canopy w/split roof, o/a 72 in. Lg, 58 in. W, 78 in h; cooler station c/o frame, full roller grille w/nobottom; 6 round wire baskets w/handles11 in dia, 4 in. D, mesh 3/4 in. Sq

N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A23800
Mil-std (military Standard):

Mil-f-38762 spec.