

View Online at <https://aerobasegroup.com/nsn/6635-01-161-4551>

Carrying Case:

Provided

Accessory Components And Quantity:

Battery 6hr 2 sets, battery cable 1 ea, battery charger/eliminator 1 ea, charger interconnect cable 1 ea, pwr cord 1 ea, op manual 1 ea, roll of 1 in w polytetrafluoroethylene tape 1 ea, 30 khz probe 1 ea, 60 khz probe 1 ea, 110 khz probe 1 ea, 165 khz probe 1 ea, 250 khz probe 1 ea, 330 khz probe 1 ea, pitch probe impulse 1 ea, pitch catch probe swept 1 ea, mechanical impedance probe 1 ea, 11 pin to 11 pin probe cable 1e, 11 pin to 4 pin probe cable 1 ea, protective carrying case 1 ea

Usage Design:

External

Indicator Type:

Electron-ray tube

Installation Design:

Portable

Test Type:

Distortion

Indicator Reading Type:

Multiple

Indicator Design:

Direct reading

Special Features:

Freq rng 500 hz to 1 mhz; gain rng 0 to 50 db

Functional Description:

Used for ultrasonic bond testing equipment of mrtallic & nonmetallic composite material

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T264-b