

View Online at <https://aerobasegroup.com/nsn/6635-01-161-4551>

**Carrying Case:**

Provided

**Accessory Components And Quantity:**

Battery 6hr 2 sets, battery cable 1 ea, battery charger/eliminator 1 ea, charger interconnect cable 1 ea, pwr cord 1 ea, op manual 1 ea, roll of 1 in w polytetrafluoroethylene tape 1 ea, 30 khz probe 1 ea, 60 khz probe 1 ea, 110 khz probe 1 ea, 165 khz probe 1 ea, 250 khz probe 1 ea, 330 khz probe 1 ea, pitch probe impulse 1 ea, pitch catch probe swept 1 ea, mechanical impedance probe 1 ea, 11 pin to 11 pin probe cable 1e, 11 pin to 4 pin probe cable 1 ea, protective carrying case 1 ea

**Usage Design:**

External

**Indicator Type:**

Electron-ray tube

**Installation Design:**

Portable

**Test Type:**

Distortion

**Indicator Reading Type:**

Multiple

**Indicator Design:**

Direct reading

**Special Features:**

Freq rng 500 hz to 1 mhz; gain rng 0 to 50 db

**Functional Description:**

Used for ultrasonic bond testing equipment of mrtallic & nonmetallic composite material

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T264-b