Stationary Magnetic Inspection Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6635-01-362-9184

Current Type:

Ac

Furnished Items And Quantity:

Dcontactor block w/connectors; 15-ft no. 4/0 cables w/connectors on bothends 2; 10 ft no. 2/0 cables w/no. 4/0connectors on both ends 2; contact prods w/no. 4/0 connectors 1 pair; contact clamps w/no. 4/0 connectors 2; fluorescent dry concentrates, 1 pound; 100 cub. Cm. Centrifuge tube 1; centrifugetube stand 1; hose brush 1; drain hose1; copper rod, 1 in. Dia. By 18 in. Lg. 1; residual field indicator 1; canopy (black light inspection) 1; black light

Automatic Cycle Timer:

Not included

Voltage In Volts:

200.0 and 460.0

Phase:

Three

Special Features:

C/o control panel, headstock, instrument panel; grille; hose; coil; tailstock; rail; base frame

Frequency In Hertz:

50.0 or 60.0

Reference Data And Literature:

Mil-m-6867c, typii54

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T264-a

Mil-std (military Standard):

Mil-m-6867 spec.