

View Online at <https://aerobasegroup.com/nsn/6635-01-381-1174>

**Carrying Case:**

Provided

**Usage Design:**

External

**Indicator Type:**

Electron-ray tube

**Installation Design:**

Portable

**Test Type:**

Distortion

**Indicator Reading Type:**

Single

**Indicator Design:**

Direct reading

**Special Features:**

C/o sonicator, oper guide, pwr cord, certification, 10vdc battery pack w/9 four-amp-hour size d cells (3 strings)& contact probe; freq 7, 14, 25, 40, 54, 84 & 130 khz; lcd display of freq, phase, signal amplitude; screen size 2.25 in. By 4.25 in.; sample rate, sinewavecycle, drive voltage, analog grain, vertical/horizontal scales, pre-amp; total freq 5-200 khz; audio, visual ttl outputalarms; 16-bit microprocessor; batterycharger; bnc connectors; rs-232; 115-230 vac, 50-60 hz; 6.5 in h, 10.5 in. W, 14.5 in. Dp; 20 lbs

**Functional Description:**

Used for ultrasonic bond testing equipment of mrtallic & nonmetallic composite material

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T264-b