

View Online at <https://aerobasegroup.com/nsn/6635-01-381-4963>

Mounting Type:

Bench

Current Type:

Ac

Prime Mover Horsepower Rating:

0.16

Drive Type:

Belt

Angular Unbalance Location Method:

Stroboscopic lamp

Maximum Working Weight Capacity:

18.0 pounds

Swing Maximum Diameter:

2.000 inches

Work Support Type:

Hard bearing

Voltage In Volts:

110.0 or 220.0

Phase:

Single

Special Features:

C/o machine bed: 19.8 in. Lg; 1.8in. H; 2 t-slots for locking bearing pedestals and air drive assembly; scale; steel workbench: 35.4 in. Lg, 23.6 in. Dp, 34.4 in. H; 2 hard-bearing supportseach w/electro-dynamic high-output pickup, flat support bridge for mounting on balancing fixture or for attachmentof horn assembly; photoelectric scanning head w/mounting stand; air drive, size 0/1/2; belt drive size 1/10, overslung; 0.4 in. W; belt drive balancing speed over 2 in. Driven diameter base speed: 2200 rpm; variable speed dc motor, 3000 rpm maximum (base speed); cab 720: color crt digital monitor and vector meter display; mtg tools; universal horn assembly; 2 oper manuals; printer; 2 saddle bearing inserts (4 in. Bore); rotor: maximum wt 36 lb; maximum sensitivity per plane: 180 rpm-1.4 gram-in, 390 rpm 0.14 gram-in, 820 rpm-0.014 gram-in, 1800 rpm-0.0014 gram-in; speed range: 100-10, 000 rpm; unbalance reduction up to 95 pct

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T137-e