

View Online at <https://aerobasegroup.com/nsn/6635-01-394-5926>

Current Type:

Ac

Accessory Components And Quantity:

Operation and maintenance manual 1; tube head ruggedized transit case 1; controller ruggedized transit case 1; cooler ruggedized transit case 1; cabling and hose ruggedized transit case 1; 2 extra keys for control unit safety lock 1; power cable assembly 100 ft with strain relief 1; control cable assembly 100 ft with strain relief 1; cooler power cable 50 ft with strain relief 1; coolant hose-twin, 50 ft, self-sealing termination 1; interlock mating connector 1; lightweight laser pointer, removable, to provide precise targeting of x-ray beam up to 50 ft

Current Rating In Amps:

10.0

Design Type:

Portable

Operation Method:

Manual

Control Type:

Mobile

Tube Quantity:

1

Tube Type:

Single focus

Tube Cooling Method:

Water

Tube Mounting Type:

Tube stand

Tube Stand Mounting Type:

Base

Radiographic Timer Type:

Exposure

Err Default:

Err default

Voltage In Volts:

100.0 and 250.0

Phase:

Single

Special Features:

N160 kvcp; x-ray tube head-directional, constant potential, end-grounded, gas insulated; control unit-digital microcomputer based; tube window 0.093 in. Thick; beam angle from side w/approx 40 degrees cone of radiation

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

Mil-std (military Standard):

Mil-prf-32133 spec.