

View Online at <https://aerobasegroup.com/nsn/6635-01-396-2798>

**Current Type:**

Ac and dc

**Furnished Items And Quantity:**

Copper rod 1; aux cables 4; 100 watt black light 1; hood 1; set of curtains 1; white light source 1; ventilation fan 1; set of copper braid pads for headstock and tailstock contact pads1; suspension tank 1; hoses with spraynozzles; agitation system 1; curcuit breaker box 1; air pressure regulator 1; air filter

**Current Rating In Amps:**

5000.0 or 6000.0

**Maximum Demagnetizing Current Rating In Amps:**

5000.0

**Err Default:**

Err default

**Automatic Cycle Timer:**

Not included

**Err Default:**

Err default and err default

**Voltage In Volts:**

200.0 and 480.0

**Phase:**

Three

**Special Features:**

Max contact head opening 52 in. Porm 2 in.; wet horizontal machine; output: dc 6000 amps with not more than 6pct ripple, ac 5000 amps; digital ammeter displays ac rms amps or dc amps atcoil or contacts; current continuouslyvariable; headstock pressure foot switch activated; input air pressure 80-90psi

**Frequency In Hertz:**

50.0 or 60.0

**Functional Description:**

Capable of magnetizing workpiecesin logitudinal and circular directionsof ferromagnetic parts

**Specification Data:**

81348-a-a-58049 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T264-a