

View Online at <https://aerobasegroup.com/nsn/6635-01-396-2798>

Current Type:

Ac and dc

Furnished Items And Quantity:

Copper rod 1; aux cables 4; 100 watt black light 1; hood 1; set of curtains 1; white light source 1; ventilation fan 1; set of copper braid pads for headstock and tailstock contact pads1; suspension tank 1; hoses with spraynozzles; agitation system 1; curcuit breaker box 1; air pressure regulator 1; air filter

Current Rating In Amps:

5000.0 or 6000.0

Maximum Demagnetizing Current Rating In Amps:

5000.0

Err Default:

Err default

Automatic Cycle Timer:

Not included

Err Default:

Err default and err default

Voltage In Volts:

200.0 and 480.0

Phase:

Three

Special Features:

Max contact head opening 52 in. Porm 2 in.; wet horizontal machine; output: dc 6000 amps with not more than 6pct ripple, ac 5000 amps; digital ammeter displays ac rms amps or dc amps atcoil or contacts; current continuouslyvariable; headstock pressure foot switch activated; input air pressure 80-90psi

Frequency In Hertz:

50.0 or 60.0

Functional Description:

Capable of magnetizing workpiecesin logitudinal and circular directionsof ferromagnetic parts

Specification Data:

81348-a-a-58049 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T264-a