

View Online at <https://aerobasegroup.com/nsn/6635-01-467-1626>

Current Type:

Ac

Furnished Items And Quantity:

Magnetic particle inspection machin (1), central conductor(1), cables 15'4/0 w/ee connectors(2), cables 10' 2/0 2/0 w/ee connectors(2), blacklight adjust arm swivel assembly(1), bh hood assembly(1), 1025a blacklight head w/bulb(1, 5/7 copper pads with v block(2)

Maximum Demagnetizing Current Rating In Amps:

6000.0 and 15000.0

Err Default:

Err default

Surface Length:

73.000 inches

Automatic Cycle Timer:

Not included

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Special Features:

Max contact head opening 52" porm2": wet horizontal machine: output dc 6000 amps with maximum 6pct ripple, ac 5000 digital ammeter displays ac rms amps, or dc amps at coil/contacts: current continuously variable: headstock pressurefoot switch activated: input air pressure 80-90psi

Frequency In Hertz:

50.0 or 60.0

Functional Description:

Capable magnetizing workpieces inlongitudinal and circular directions of ferromagnetic parts. Reverses dc andac ramp demagnetization to less than 3gases

Relationship To Similar Equipment:

Similar to cid a-a58049 includes less assesories

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T264-a