

View Online at <https://aerobasegroup.com/nsn/6636-00-013-8808>

**Overall Depth:**

48.000 inches

**Overall Height:**

75.000 inches

**Overall Width:**

48.000 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 55.0 hertz and 65.0 hertz

**Inside Width:**

28.000 inches

**Inside Depth:**

26.000 inches

**Inside Height:**

30.000 inches

**Assembly Form:**

Assembled

**Closure Method:**

Hinged cover

**Compartment Quantity:**

1

**End Application:**

Chamber, environmental testing; tests altimeters aau altitude transducers cpu-46a

**Voltage Rating:**

Between 220.0 volts and 240.0 volts

**Power Rating:**

Between 350.0 watts and 1000.0 watts

**Control Type:**

Toggle switch and selector switch and bleeder valve and vacuum gage

**Opening Location:**

Left side or right side

**Operating Temperature Range In Deg Celsius:**

-73.3 to 121.0

**Heat Source For Which Designed:**

Integral

**Heating Method:**

Electrical

**Circulation Method:**

Mechanical

**Door:**

Provided

**Cooling Coils For Below Room Temperature Use:**

Included

**Outer Door Quantity:**

2

**Cubic Measure:**

172800.000 cubic inches

**Environmental Chamber Type:**

Temperature

**Product Name:**

Temperature chamber

**Phase:**

Three

**Special Features:**

Temperature chamber with removable holding rack 1 neoprene plug 4.000 in. Dia. Pressure control panel, rubber tubing ea 8.000ft lg., 3 plugs

**Material:**

Copper and rubber, chloroprene and metal

**Material:**

Copper and rubber chloroprene class cr

**Surface Treatment:**

Zinc and enamel

**Supplementary Features:**

The chamber is used for subjecting altimeters and altitude transducer computers, similar to the aau-19/a and cpu-46/a respectively, to precisely controlled temperature environments during scale error testing

**Surface Treatment:**

Zinc and enamel, black

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T269-e