

View Online at <https://aerobasegroup.com/nsn/6636-01-453-2322>

**Current Type:**

Ac

**Frequency Rating:**

60.0 hertz

**Inside Width:**

16.000 inches

**Outside Width:**

30.000 inches

**Inside Depth:**

11.000 inches

**Inside Height:**

12.000 inches

**Outside Height:**

41.000 inches

**Assembly Form:**

Assembled

**Accessory Components And Quantity:**

2 1/2 horsepower compressors

**Voltage Rating:**

115.0 volts

**Power Rating:**

40.0 volt-ampere

**Operating Temperature Range In Deg Celsius:**

-73.3/+177.0

**Heat Source For Which Designed:**

Integral

**Outside Depth:**

22.000 inches

**Heating Method:**

Electrical

**Water Jacket:**

Provided

**Circulation Method:**

Mechanical

**Door:**

Provided

**Insulated Cabinet:**

Provided

**Cooling Coils For Below Room Temperature Use:**

Included

**Cabinet Outer Wall Material:**

Steel

**Cabinet Inner Wall Material:**

Steel

**Cabinet Mounting Type:**

Stand

**Outer Door Quantity:**

1

**Outer Door Material:**

Steel

**Outer Door Insulation Feature:**

Included

**Environmental Chamber Type:**

Temperature

**Phase:**

Single

**Special Features:**

Programmable temperature controller with digital display (model 2800); 6pane thermal window with silicone gaskets; rs-232c or ieee-488 interface; dry nitrogen used to reduce moisture content; modified to include refractor collimator, motorized target wheel and vibration isolated base plate; used to test the b-52 flir sensor assembly (an/aaq-23) and used in conjunction with ir radiation source control unit sr-80-2d

**Color:**

Blue

**Material:**

Steel

**Material:**

Steel

**Surface Treatment:**

Lacquer, federal specification 595-25185

**Surface Treatment:**

Lacquer, federal specification 595-25185

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T269-e