## NSN 6645-00-727-5119

Time Totalizing Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6645-00-727-5119

Terminal Type: Solder lug Mounting Type: Panel Current Type: Ac Body Length: 0.680 inches Mounting Flange Width: 1.310 inches Case Material: Metal Inscription Color: Black or black Inscription Background Color: White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Terminal Quantity:
Solder lug  Mounting Type: Panel  Current Type: Ac  Body Length: 0.680 inches  Mounting Flange Width: 1.310 inches  Case Material: Metal Inscription Color: Black or black Inscription Background Color: White or white  Flange Height: 0.875 inches  Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial  Voltage Rating: 115.0 volts  Unit Type: Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	2
Mounting Type: Panel Current Type: Ac Body Length: 0.680 inches Mounting Flange Width: 1.310 inches Case Material: Metal Inscription Color: Black or black Inscription Background Color: White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Terminal Type:
Panel Current Type: Ac Body Length: 0.680 inches Mounting Flange Width: 1.310 inches Case Material: Metal Inscription Color: Black or black Inscription Background Color: White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Solder lug
Current Type: Ac Body Length: 0.680 inches Mounting Flange Width: 1.310 inches Case Material: Metal Inscription Color: Black or black Inscription Background Color: White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Mounting Type:
Body Length: 0.680 inches Mounting Flange Width: 1.310 inches Case Material: Metal Inscription Color: Black or black Inscription Background Color: White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Panel
Body Length:  0.680 inches  Mounting Flange Width:  1.310 inches  Case Material:  Metal  Inscription Color:  Black or black  Inscription Background Color:  White or white  Flange Height:  0.875 inches  Mounting Configuration:  Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c  Indicator Type:  Indicator dial  Voltage Rating:  115.0 volts  Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection:  Not provided  Movement Type:  Electrical  Body Depth:  1.245 inches  Pointer Quantity:	Current Type:
Mounting Flange Width:  1.310 inches  Case Material:  Metal  Inscription Color:  Black or black  Inscription Background Color:  White or white  Flange Height:  0.875 inches  Mounting Configuration:  Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c  Indicator Type:  Indicator dial  Voltage Rating:  115.0 volts  Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection:  Not provided  Movement Type:  Electrical  Body Depth:  1.245 inches  Pointer Quantity:	Ac
Mounting Flange Width:  1.310 inches  Case Material:  Metal  Inscription Color:  Black or black Inscription Background Color:  White or white  Flange Height:  0.875 inches  Mounting Configuration:  Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial  Voltage Rating:  115.0 volts  Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth:  1.245 inches  Pointer Quantity:	Body Length:
1.310 inches  Case Material:  Metal  Inscription Color:  Black or black  Inscription Background Color:  White or white  Flange Height: 0.875 inches  Mounting Configuration:  Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c  Indicator Type: Indicator dial  Voltage Rating: 115.0 volts  Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection:  Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	0.680 inches
Case Material:  Metal  Inscription Color:  Black or black  Inscription Background Color:  White or white  Flange Height: 0.875 inches  Mounting Configuration:  Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial  Voltage Rating: 115.0 volts  Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	Mounting Flange Width:
Metal Inscription Color: Black or black Inscription Background Color: White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	1.310 inches
Inscription Color: Black or black Inscription Background Color: White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Case Material:
Black or black Inscription Background Color: White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Metal
Inscription Background Color: White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Inscription Color:
White or white Flange Height: 0.875 inches Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Black or black
Flange Height:  0.875 inches  Mounting Configuration:  Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial  Voltage Rating:  115.0 volts  Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	Inscription Background Color:
Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	White or white
Mounting Configuration: Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Flange Height:
Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c Indicator Type: Indicator dial  Voltage Rating: 115.0 volts Unit Type: Mounted Scale Range: +0.0/+99.0 hour Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	0.875 inches
Indicator Type: Indicator dial  Voltage Rating: 115.0 volts  Unit Type: Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	Mounting Configuration:
Indicator dial  Voltage Rating:  115.0 volts  Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	Two no. 0.125 in. Diameter holes spaced 1.000 in. C to c
Voltage Rating:  115.0 volts  Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	Indicator Type:
115.0 volts  Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	Indicator dial
Unit Type:  Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	Voltage Rating:
Mounted  Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	115.0 volts
Scale Range: +0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical Body Depth: 1.245 inches  Pointer Quantity:	Unit Type:
+0.0/+99.0 hour  Operating Frequency: 400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	Mounted
Operating Frequency: 400.0 hertz Hermetic Protection: Not provided Movement Type: Electrical Body Depth: 1.245 inches Pointer Quantity:	Scale Range:
400.0 hertz  Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	+0.0/+99.0 hour
Hermetic Protection: Not provided  Movement Type: Electrical  Body Depth: 1.245 inches  Pointer Quantity:	Operating Frequency:
Not provided  Movement Type:  Electrical  Body Depth:  1.245 inches  Pointer Quantity:	400.0 hertz
Movement Type:  Electrical  Body Depth:  1.245 inches  Pointer Quantity:	Hermetic Protection:
Electrical  Body Depth:  1.245 inches  Pointer Quantity:	Not provided
Body Depth: 1.245 inches Pointer Quantity:	Movement Type:
1.245 inches  Pointer Quantity:	Electrical
Pointer Quantity:	Body Depth:
	1.245 inches
	Pointer Quantity:
2	2

Dial Diameter:

0.680 inches

## NSN 6645-00-727-5119

Time Totalizing Meter - Page 2 of 2



Pointer Color:
Black
Scale Smallest Increment:
1.00 hours
Mounting Method:
Semiflush
Reset Feature:
Not provided
Electrical Movement Type:
Synchronous motor
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T134-r