

View Online at <https://aerobasegroup.com/nsn/6645-01-469-9063>

**Overall Depth:**

1.250 inches

**Overall Height:**

2.000 inches

**Overall Width:**

2.000 inches

**Current Type:**

Ac and dc

**Mounting Method:**

Surface

**Timer Type:**

Electrical

**Reset Type:**

Electric

**Dc Operated Clutch:**

Not included

**Control Type:**

Switch

**Automatic Electric Circuit Control Switch:**

Not included

**Independently Operated Clock:**

Not included

**Product Name:**

Solid-state cube timer

**Voltage In Volts:**

24.0

**Special Features:**

Time delay adjustment is through an external resistor (1 megohm maximum to 0.250 watt min. Recommended) with a range of 0.5 to 10.0 seconds; reverse polarity protection; flame retardent and solvent resistant polyester thermoplastic housing; output type, solid state, normally open; 1 amp steady state output rating; transient voltage protection through metal oxide varistor; dielectric breakdown, 3000 vac, rms, terminals to mounting; insulation resistance 100 megaohms between terminals and case; terminals (7) are 0.250 in. By 0.032 in. Male fast-on; unit is mounted using one no. 8 screw through 0.170 in. Unthreaded hole located in center of face; storage temperature minus 40 to plus 85 deg. C; operating temperature minus 40 to plus 65 deg. C; humidity to 95 percent relative

**Frequency In Hertz:**

50.0 or 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T270-d