

View Online at <https://aerobasegroup.com/nsn/6645-01-469-9065>

Overall Depth:

1.250 inches

Overall Height:

2.000 inches

Overall Width:

2.000 inches

Current Type:

Ac and dc

Mounting Method:

Surface

Timer Type:

Electrical

Reset Type:

Electric

Dc Operated Clutch:

Not included

Control Type:

Switch

Automatic Electric Circuit Control Switch:

Not included

Independently Operated Clock:

Not included

Product Name:

Solid-state cube timer

Voltage In Volts:

24.0

Special Features:

Time delay adjustment is through an external resistor (1 megohm maximum to 0.250 watt min. Recommended) with a range of 3.0 to 60.0 minutes; reverse polarity protection; flame retardent and solvent resistant polyester thermoplastic housing; output type, solid state, normally open; 1 amp steady state output rating; transient voltage protection through metal oxide varistor; dielectric breakdown, 3000 vac, rms, terminals to mounting; insulation resistance 100 megaohms between terminals and case; terminals (7) are 0.250 in. By 0.032 in. Male fast-on; unit is mounted using one no. 8 screw through 0.170 in. Unthreaded hole located in center of face; storage temperature minus 40 to plus 85 deg. C; operating temperature minus 40 to plus 65 deg. C; humidity to 95 percent relative

Frequency In Hertz:

50.0 or 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T270-d