## NSN 6660-01-375-4809

Cloud Height Indicator Set - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6660-01-375-4809

Document Source:  97384  Document Type: Eengineering handbook  Component Document Page Number:  9-1  Package Model Number:  Ct12k  Document Identification:
Unpackaged Unit Length: 29.100 inches Unpackaged Unit Width: 22.800 inches Unpackaged Unit Height: 16.500 inches Component Quantity: 37 Component Document Origin: Government Document Source: 97384 Document Type: Eengineering handbook Component Document Page Number: 9-1 Package Model Number: Ct12k Document Identification:
29.100 inches Unpackaged Unit Width: 22.800 inches Unpackaged Unit Height: 16.500 inches Component Quantity: 37 Component Document Origin: Government Document Source: 97384 Document Type: Eengineering handbook Component Document Page Number: 9-1 Package Model Number: Ctt2k Document Identification:
Unpackaged Unit Width:  22.800 inches  Unpackaged Unit Height: 16.500 inches  Component Quantity: 37  Component Document Origin: Government  Document Source: 97384  Document Type: Eengineering handbook  Component Document Page Number: 9-1  Package Model Number: Ctt2k  Document Identification:
22.800 inches Unpackaged Unit Height: 16.500 inches Component Quantity: 37 Component Document Origin: Government Document Source: 97384 Document Type: Eengineering handbook Component Document Page Number: 9-1 Package Model Number: Ctt2k Document Identification:
Unpackaged Unit Height: 16.500 inches  Component Quantity: 37  Component Document Origin: Government  Document Source: 97384  Document Type: Eengineering handbook  Component Document Page Number: 9-1  Package Model Number: Ct12k  Document Identification:
16.500 inches  Component Quantity: 37  Component Document Origin: Government  Document Source: 97384  Document Type: Eengineering handbook  Component Document Page Number: 9-1  Package Model Number: Ct12k  Document Identification:
Component Quantity: 37 Component Document Origin: Government Document Source: 97384 Document Type: Eengineering handbook Component Document Page Number: 9-1 Package Model Number: Ct12k Document Identification:
Component Document Origin: Government Document Source: 97384 Document Type: Eengineering handbook Component Document Page Number: 9-1 Package Model Number: Ct12k Document Identification:
Component Document Origin: Government  Document Source: 97384  Document Type: Eengineering handbook  Component Document Page Number: 9-1  Package Model Number: Ct12k  Document Identification:
Government  Document Source:  97384  Document Type: Eengineering handbook  Component Document Page Number:  9-1  Package Model Number:  Ct12k  Document Identification:
Government  Document Source:  97384  Document Type: Eengineering handbook  Component Document Page Number:  9-1  Package Model Number:  Ct12k  Document Identification:  W/os0321: bgm
97384  Document Type: Eengineering handbook  Component Document Page Number: 9-1  Package Model Number: Ct12k  Document Identification:
Document Type: Eengineering handbook Component Document Page Number: 9-1 Package Model Number: Ct12k Document Identification:
Eengineering handbook  Component Document Page Number:  9-1  Package Model Number:  Ct12k  Document Identification:
Component Document Page Number: 9-1 Package Model Number: Ct12k Document Identification:
9-1  Package Model Number:  Ct12k  Document Identification:
Package Model Number: Ct12k  Document Identification:
Ct12k  Document Identification:
Document Identification:
W/os0321: bgm
Special Features:
C/o 2 subassys: 1) optics subassy: transmitter board, receiver board, optics hardware, light monitor board, transmitter/receiver lens, temp
compensation transformer, 2 temp control heaters, solar shutter not incl, 7 cables, 4 connectors; 2) electronics subassy: base, power supp
housing, board frame, high voltage power supply, processor board, unregulated power supply board, i/o connector board, fiberoptic module
temp sensor, 4 connectors; 116 vac, 45-65 hz, 800 wk; gallium arsenide laser; 904 nm wavelength; pulsed; 40 wpeak, 1.3 x 1.3 mm lase
dimensions; focal lg 14.45 in., 4.65 in. Lens dia; lens transmit 90 pct; silicon avalanche photodiode detector; optical: lens distance 12.2
in., 100 ft laser beam entering recvr fov; measurement range: 0-12, 650 ft; mounted on pedestal approximately 23 in. High
Functional Description:
Uses invisible laser radiation todetect cloud levels
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A23800